

HEBEBÄNDER & RUNDSCHLINGEN

Benutzerinformation Hebebänder / Rundschlingen

- Hebebänder/Rundschlingen nur zum Heben und Transportieren von Lasten verwenden.
- Hebebänder/Rundschlingen dürfen nur von unterwiesenen und beauftragten Personen verwendet werden.
- Hebebänder/Rundschlingen niemals über ihre Tragfähigkeit hinaus belasten! Geeignete Hebebänder/Rundschlingen, Anschlagpunkte und Anschlagarte auswählen.
- Beachten Sie hierbei z.B.:
 - Gewicht, Schwerpunkt, Abmessungen und Oberfläche der Last.
 - Neigungswinkel (max. 60°). Lastanschlagfaktoren.
 - Einsatzbereich: Temperaturbereich, Chemikalieneinsatz etc. Eine falsche Auswahl kann zum Bruch des Hebebandes/der Rundschlinge führen!
- Hebebänder/Rundschlingen vor jedem Einsatz auf Schäden überprüfen.
- Verwendung nur im Temperaturbereich: -40°C bis +100°C (PES und PA) bzw. bis +80°C (PP).
- Einsatz in Chemikalien kann das Hebeband/die Rundschlinge zerstören! Unbedingt unsere Informationen einholen. Reinigung nur mit Wasser.
- Bei scharfen Kanten dürfen Hebebänder/Rundschlingen nur mit geeigneten Kantenschonern (z.B. aus PU, Mindestdicke 5mm) eingesetzt werden. PVC- und PU-Schutzmanschetten dienen nur als Abriebsschutz und schützen nicht vor scharfen Kanten!
- Hebebänder/Rundschlingen sollen mit ihrer ganzen Breite tragen.
- Geknotete oder abgelegte Hebebänder/Rundschlingen dürfen nicht verwendet werden.
- Überprüfung durch Sachkundigen mind. 1x jährlich.
- Unsachgemäßer Umgang mit Hebebändern/Rundschlingen stellt eine Gefahr für das Leben von Personen und Gütern dar. Insbesondere ist die Person unter oder neben der Last gefährdet. Vorsicht vor pendelnder Last!
- Beachten Sie unsere ausführliche Betriebsanleitung sowie die Vorschriften und Hinweise der UWVGB 9a, EN 1492-1/-2, ZH 1/103a und ZH 1/324.

User's information Lifting Slings / Round Slings

- User lifting slings/round slings only to lift and transport loads.
- Lifting slings/round slings may be used only by authorized person who have previously received instruction in their use.
- Never load lifting slings/round slings beyond their carrying methods.
- Select suitable lifting slings/round slings, slinging points and methods. Important points to observe here are, e.g.:
 - Weight, centre of gravity, dimensions and surface of the load.
 - Angle of inclination (max. 60°) load slinging factors.
 - Area of application: temperature range, chemical application, etc. The wrong choice can result in the lifting slings/round slings breaking!
- Always check the lifting slings/round slings before use for any signs of damage.
- Lifting slings/round slings may be used only for the temperature range: -40°C to +100°C (PES and PA) or up to +80°C (PP)
- Using the slings in chemicals can destroy the webbing! In such cases it is essential to ask us for further information. For cleaning use only water.
- In case of sharp edges, lifting slings/round slings may be used only with appropriate edge coverings (e.g. made of PU with a minimum thickness of 5mm). PVC and PU protective strips are intended only to protect against sharp edges!
- The entire width of the lifting slings/round slings should be used when lifting.
- Do not use knotted lifting slings/round slings or ones which should be discarded.
- The slings should be checked by an expert at least once a year.
- Incorect use of lifting slings/round slings represents a danger to human life and to goods. The person below or next to the load is particularly at risk. Observe great caution when working with swinging loads!
- Please observe the information in our detailed instruction manual and the information in UW VGB 9a, EN 1492-1/-2, ZH 1/103a and ZH 1/324.

MT Onlineshops GmbH

Werner-von-Siemens-Straße 12-14
36041 Fulda

Telefon: +49 (661) 380 9988-0

Fax: +49 (661) 380 9988-9

E-Mail: info@ladungssicherung.eu

Internet: www.ladungssicherung.eu

lasiprofi

Ladungssicherung für Profis.