

PRODUCT - INFORMATION

Bag 3D

Dunnage bag for Load Securement

2-Layers 1xPE / 1xPP



Inner layer:	Material:	Polyethylen (PE) foil
	Thickness:	100 µm structure-optimized
	Spec. weight:	92 g/m ²
	Function:	Air chamber
Outer layer:	Material:	Woven Polypropylene with lamination
	Weight:	155 g/m ²
	Function:	<ul style="list-style-type: none">- Protects the inner layer from damage- Provides form and stabilizes the dunnage bag
Disposal and Environment:		<ul style="list-style-type: none">- Mutual disposal of PE and PP- Completely recyclable- Unproblematic when burned
Valve:	One way flexible Valve:	Flexible PE-tube valve with self-adhesive seal
	Reusable Valve:	Round valve with 60 mm inflation and deflation opening
Inflation:		With inflation adaptor according to the kind of valve
Recommended working pressure:		max. 0,2 bar
Recommended burst air pressure:		max. 0,6 bar measured at a void of 30 cm

MT Onlineshops GmbH

Werner-von-Siemens-Straße 12-14
36041 Fulda

Telefon: +49 (661) 380 9988-0
Fax: +49 (661) 380 9988-9
E-Mail: info@ladungssicherung.eu
Internet: www.ladungssicherung.eu

lasiprofi
Ladungssicherung für Profis.